

Multi-Vehicle ONE Coolant Premix (ONEPM)

Nulon Multi-Vehicle ONE Coolant Premix is guaranteed safe to use as a top-up for any car, 4WD, LPG or light and heavy-duty diesel vehicle on Australian and New Zealand roads. This advanced Global Type A pre-mixed coolant is a 50% mix and is safe to use as a top-up with all Green, Red, Orange and Blue OEM coolants and corrosion inhibitors. It provides the ultimate anti-freeze/anti-boil and anti-corrosion and rust protection for all vehicle cooling systems.

For a full coolant service change refer to [Nulon Long Life Coolants](#) or [Nulon ONE Coolant](#).



Directions for use

DIRECTIONS AS TOP UP: Add as top-up to existing coolant, then start the engine and turn the heater on. When the engine is warm, turn it off and allow it to cool. Check the coolant level, and top it up if necessary.

Note: The life of Nulon Multi-Vehicle ONE Coolant Premix defaults to that of the original coolant in the cooling system. If you are unaware of the type or life of the coolant in the system we recommend a complete coolant change within the next 5,000km or 6 months to the appropriate Nulon Premium Long Life Concentrated Coolant or ONE Coolant.

Typical Characteristics

Typical Properties:	
Density (g/ml @ 15.6oC)	1.072 - 1.078
Freezing point	N/A
Boiling point *	N/A
pH	8.0 - 9.0
Reserve alkalinity (ml)	2.7 min
Colour	Yellow
Glycol content (g/L)	545

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Safety Directions

SAFETY: Harmful if swallowed. May cause respiratory irritation. Use only outdoors or in a well-ventilated area. Store locked up.

FIRST AID: IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Rinse mouth. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once).

ENVIRONMENT: Do not pollute drains, soil or water with used products. After use, dispose of container in a responsible manner. Disposal of container should comply with local council regulations.

Meets or exceeds the following oil industry specifications	
AS Claims	AS 2108-2004 Type A
ASTM	ASTM D1384, ASTM D2570, ASTM D2809, ASTM D4985
Other Claims	JIS K2234 (Japan)
Society of Automotive Engineers	SAE J1034, SAE J1941

Pack Sizes



Part No: ONEPM-1
1 Litre - 6 Per Carton
Barcode: 9311090004610